



2024 Significant Drill Hole Intervals

Hole ID	From (m)	To (m)	Width (m)	% Cu
MB-24-001	52.52	93	40.48	0.1049
52.52m – 62m: 9.48m @ 0.3396% Cu	52.52	54.00	1.48	0.3780
	54.00	55.00	1.00	0.5560
	55.00	56.00	1.00	0.5220
	56.00	57.20	1.20	0.1360
	57.20	58.79	1.59	0.0275
	58.79	60.00	1.21	0.6720
	60.00	61.00	1.00	0.3420
	61.00	62.00	1.00	0.2200
	62.00	63.50	1.50	0.0296
	63.50	65.00	1.50	0.0218
	65.00	66.75	1.75	0.0071
	66.75	68.25	1.50	0.0112
	68.25	70.00	1.75	0.0266
	70.00	71.80	1.80	0.0129
	71.80	73.20	1.40	0.0047
	73.20	75.00	1.80	0.0102
	75.00	77.00	2.00	0.0093
77.00	78.50	1.50	0.0070	
78.50	80.00	1.50	0.0064	
80.00	81.50	1.50	0.0050	
81.50	83.00	1.50	0.0151	
83.00	84.00	1.00	0.0300	
84.00	85.00	1.00	0.0063	
85.00	86.00	1.00	0.1040	
86.00	87.37	1.37	0.0235	
87.37	87.95	0.58	0.0393	
87.95	89.00	1.05	0.0282	
89.00	90.00	1.00	0.0659	
90.00	91.00	1.00	0.2020	
91.00	92.00	1.00	0.0301	
2.00	93.00	1.00	0.2360	
MB-24-004	18.34	46.66	28.32	0.1123
	18.34	19.87	1.53	0.1320
	19.87	21.00	1.13	0.1040
	21.00	23.00	2.00	0.0198
	23.00	25.00	2.00	0.0063
	25.00	27.00	2.00	0.0069
	27.00	29.00	2.00	0.0070
	29.00	30.12	1.12	0.0135
	30.12	32.00	1.88	0.0285
	32.00	34.00	2.00	0.0235
	34.00	35.80	1.80	0.0670
35.80m – 46.66m: 10.86m @ 0.2343% Cu	35.80	36.80	1.00	0.1300
	36.80	37.80	1.00	0.3360
	37.80	38.80	1.00	0.2010
	38.80	39.80	1.00	1.1000
	39.80	40.80	1.00	0.0644
	40.80	41.80	1.00	0.1210
	41.80	42.80	1.00	0.1030
	42.80	44.00	1.20	0.1140
	44.00	45.25	1.25	0.0318
	45.25	46.66	1.41	0.2220

Hole ID	From (m)	To (m)	Width (m)	% Cu
NC-24-001	313.68	370.30	56.62	0.1700
	313.68	315.20	1.52	0.2270
	315.20	316.70	1.50	0.0224
	316.70	318.00	1.30	0.0695
	318.00	318.90	0.90	0.2230
	318.90	320.40	1.50	0.2970
	320.40	321.90	1.50	0.1070
	321.90	323.40	1.50	0.0553
	323.40	324.90	1.50	0.0307
	324.90	326.40	1.50	0.1100
	326.40	327.60	1.20	0.1110
	327.60	329.20	1.60	0.0556
	329.20	330.20	1.00	0.0048
	330.20	331.00	0.80	0.0120
	331.00	332.00	1.00	0.0066
	332.00	333.50	1.50	0.0393
	333.50	335.00	1.50	0.0621
	335.00	336.50	1.50	0.0103
336.50m – 370.30m: 33.80m @ 0.2262% Cu	336.50	338.00	1.50	0.1160
	338.00	339.00	1.00	0.1100
	339.00	341.00	2.00	0.2790
	341.00	343.00	2.00	0.4560
	343.00	344.42	1.42	0.2750
	344.42	346.00	1.58	0.0320
	346.00	347.50	1.50	0.0398
	347.50	349.00	1.50	0.0114
	349.00	350.50	1.50	0.0787
	350.50	351.50	1.00	0.1150
	351.50	352.00	0.50	1.0000
	352.00	353.00	1.00	0.0750
	353.00	354.00	1.00	0.4250
	354.00	355.00	1.00	0.0373
	355.00	356.00	1.00	0.9930
	356.00	357.00	1.00	0.1950
	357.00	358.00	1.00	0.2730
	358.00	359.00	1.00	0.4800
	359.00	360.00	1.00	0.1440
	360.00	361.00	1.00	0.1440
	361.00	362.00	1.00	0.1070
	362.00	363.00	1.00	0.4630
	363.00	364.00	1.00	0.2360
364.00	365.00	1.00	0.1560	
365.00	366.00	1.00	0.2110	
366.00	367.00	1.00	0.1300	
367.00	368.00	1.00	0.1310	
368.00	369.00	1.00	0.0881	
369.00	370.30	1.30	0.1660	
NC-24-001	404.00	479.00	75	0.3636
	404.00	405.00	1.00	0.2700
	405.00	406.00	1.00	0.6620
	406.00	407.00	1.00	0.2050
	407.00	408.00	1.00	0.0005
	408.00	409.00	1.00	0.0051
	409.00	410.00	1.00	0.0074
	410.00	411.00	1.00	0.0009
	411.00	412.00	1.00	0.1420
	412.00	413.00	1.00	1.0000
	413.00	414.00	1.00	0.1940
	414.00	415.00	1.00	0.1770
	415.00	416.00	1.00	0.4300
	416.00	417.00	1.00	0.0651
	417.00	418.00	1.00	0.1030
	418.00	419.00	1.00	0.0114

Hole ID	From (m)	To (m)	Width (m)	% Cu
	419.00	420.00	1.00	0.0218
	420.00	421.00	1.00	0.0469
	421.00	422.00	1.00	0.0300
	422.00	423.00	1.00	0.1710
	423.00	424.00	1.00	0.1020
	424.00	425.00	1.00	0.0563
425.00m – 435.00m: 10m @ 0.9708% Cu	425.00	426.00	1.00	0.2030
	426.00	427.00	1.00	0.7630
	427.00	428.00	1.00	0.3970
	428.00	429.00	1.00	0.2240
	429.00	430.00	1.00	0.1510
	430.00	431.00	1.00	0.2040
	431.00	432.00	1.00	1.0000
	432.00	433.00	1.00	1.0000
	433.00	434.00	1.00	1.0000
	434.00	435.00	1.00	0.4860
	435.00	436.00	1.00	0.0876
	436.00	437.00	1.00	0.0465
	437.00	438.00	1.00	0.0761
	438.00	439.00	1.00	0.0827
	439.00	440.00	1.00	0.0397
	440.00	441.00	1.00	0.0892
	441.00	442.00	1.00	0.1340
	442.00	443.00	1.00	0.0883
	443.00	444.00	1.00	0.5200
	444.00	445.00	1.00	0.6720
	445.00	446.00	1.00	0.0054
	446.00	447.00	1.00	0.0044
	447.00	448.00	1.00	0.0136
	448.00	449.00	1.00	0.0450
	449.00	450.00	1.00	0.0299
	450.00	451.00	1.00	0.0285
	451.00	452.00	1.00	0.0470
	452.00	453.00	1.00	0.0028
	453.00	454.00	1.00	0.0139
	454.00	455.00	1.00	0.0283
	455.00	456.00	1.00	0.2330
	456.00	457.00	1.00	0.0109
	457.00	458.00	1.00	0.0461
	458.00	459.00	1.00	0.0648
	459.00	460.00	1.00	0.0524
	460.00	461.00	1.00	0.0004
	461.00	462.00	1.00	0.0007
	462.00	463.00	1.00	0.1340
	463.00	464.00	1.00	0.1590
	464.00	465.00	1.00	0.0759
	465.00	466.00	1.00	0.0138
466.00m – 478.00m: 12m @ 0.8510% Cu	466.00	467.00	1.00	0.5160
	467.00	468.00	1.00	0.4990
	468.00	469.00	1.00	0.1580
	469.00	470.00	1.00	0.6410
	470.00	471.00	1.00	1.0000
	471.00	472.00	1.00	0.6490
	472.00	473.00	1.00	0.2800
	473.00	474.00	1.00	0.0603
	474.00	475.00	1.00	0.1640
	475.00	476.00	1.00	0.2980
	476.00	477.00	1.00	0.3730
	477.00	478.00	1.00	0.4140
	478.00	479.00	1.00	0.1930
NC-24-002	344.10	397.00	52.9	1.031
	344.10	345.20	1.10	0.2350

Hole ID	From (m)	To (m)	Width (m)	% Cu
	345.20	346.00	0.80	0.4180
	346.00	347.47	1.47	0.0528
	347.47	349.00	1.53	0.2790
	349.00	350.52	1.52	0.3940
	350.52	353.57	3.05	0.1260
	353.57	355.00	1.43	0.0501
	355.00	356.00	1.00	0.0285
	356.00	357.00	1.00	0.0238
	357.00	358.50	1.50	0.1160
	358.50	359.75	1.25	0.1710
359.75m – 372.75m: 13.00m @ 3.464% Cu	359.75	360.75	1.00	7.9100
	360.75	361.75	1.00	4.4200
	361.75	362.75	1.00	7.7000
	362.75	363.75	1.00	6.0600
	363.75	364.75	1.00	1.8300
	364.75	365.76	1.01	1.9500
	365.76	366.75	0.99	0.9380
	366.75	367.75	1.00	2.9200
	367.75	368.75	1.00	2.4900
	368.75	369.75	1.00	5.6300
	369.75	370.75	1.00	0.3280
	370.75	371.75	1.00	1.1000
	371.75	372.75	1.00	1.7500
	372.75	373.75	1.00	0.1470
	373.75	374.75	1.00	0.5660
	374.75	375.75	1.00	0.1690
	375.75	376.75	1.00	0.2180
	376.75	377.75	1.00	0.4980
	377.75	379.00	1.25	0.3390
	379.00	380.00	1.00	0.5620
	380.00	381.00	1.00	0.5080
	381.00	382.00	1.00	0.6400
	382.00	383.00	1.00	0.3800
	383.00	384.00	1.00	0.8550
	384.00	385.00	1.00	0.0703
	385.00	386.00	1.00	0.1250
	386.00	387.00	1.00	0.0069
	387.00	388.00	1.00	0.3350
	388.00	389.00	1.00	0.0986
	389.00	390.00	1.00	0.0139
	390.00	391.00	1.00	0.3080
	391.00	392.00	1.00	0.0799
	392.00	393.00	1.00	0.0420
	393.00	394.00	1.00	0.0296
	394.00	395.00	1.00	0.0094
	395.00	396.00	1.00	0.6380
	396.00	397.00	1.00	0.1750

Qualified Person

William Whitty, P. Geo., the Company's VP Exploration, is the Qualified Person as defined by National Instrument 43-101 - *Standards of Disclosure for Mineral Projects* and supervised the preparation of, and has reviewed and approved the technical information in this table. A summary of results and conclusions, including collar locations of the 2024 drill program are in the [February 20, 2025 News Release](#).